

AC/DC power Adapter

AN119- 24W desktop type



CB



C E

Item No.	Input Voltage	Output Voltage	Output current	Output power	Efficiency	Total adjustment rate
AN119w24-3.3V4A	100~240V	3.3V	4.0A	12W	70%	.+/-5%
AN119w24-4.2V4A	100~240V	4.2V	4.0A	17W	70%	.+/-5%
AN119w24-4.5V4A	100~240V	4.5V	4.0A	18W	70%	.+/-5%
AN119w24-5.0V4A	100~240V	5.0V	4.0A	20W	70%	.+/-5%
AN119w24-6.0V4A	100~240V	6.0V	4.0A	24W	68%	.+/-5%
AN119w24-7.5V3.2A	100~240V	7.5V	3.2A	24W	70%	.+/-5%
AN119w24-8.4V2.85A	100~240V	8.4V	2.85A	24W	70%	.+/-5%
AN119w24-9.0V2.6A	100~240V	9.0V	2.6A	24W	75%	.+/-5%
AN119w24-12.0V2A	100~240V	12.0V	2.0A	24W	78%	.+/-5%
AN119w24-12.6V1.9A	100~240V	12.6V	1.9A	24W	78%	.+/-5%
AN119w24-15V1.6A	100~240V	15.0V	1.6A	24W	80%	.+/-5%
AN119w24-16.8V1.42A	100~240V	16.8V	1.42A	24W	80%	.+/-5%
AN119w24-18.0V1.3A	100~240V	18.0V	1.3A	24W	82%	.+/-5%
AN119w24-21.0V1.2A	100~240V	21.0V	1.2A	24W	82%	.+/-5%
AN119w24-24.0V1A	100~240V	24.0V	1.0A	24W	82%	.+/-5%
AN119w24-27.0V0.9A	100~240V	27.0V	0.9A	24W	82%	.+/-5%
AN119w24-36.0V0.65A	100~240V	36.0V	0.65A	24W	82%	.+/-5%

Key Specifications

1) Input:

- a) Universal AC voltage , or Linear voltage
- b) Frequency: 50/60Hz
- c) Line regulation range: max. $\pm 0.5\%$

2) Output:

- a) Line regulation range: max. $\pm 0.5\%$
- b) Ripple and noise (Vpp): <1% of output voltage
- c) Adjustable range of output voltage: +5%, -3%
- d) Turn-on time: $\leq 1s$ @ AC input 240V and $I_o=100\%$
- e) Hold-up time: $\geq 20ms$ @ AC input 240V and $I_o=100\%$

3) Protection:

- a) Over loading protection: 115-150% of rated power, when it happened, the power shuts down automatically; when trouble removed the power recovers itself

- b) Over voltage protection: 130-150% of rated voltage
- c) Over current protection

4) Insulated intensity in-out: 1,500V/5mA, 60s

5) Insulated resistance in-out: $\geq 50\text{m}\Omega$, DC500V

6) Environmental requirements:

- a) Operating temperature: 0-40°C
- b) Operating humidity: 10-90% RH (no freezing dew)
- c) Storage temperature: -20-85°C
- d) Storage humidity: 10-95% RH (no freezing dew)

7) Elevation: <3,000m

8) Dimensions (L x W x H): 120*50*35mm or as required

9) Weight: 250g/pc or as required

10) EMC: EN55022, GB3954, CE, GS, UL, PSE, CCC, etc..

11) Storage:

- a) Warehouse temperature: -25-75°C
- b) Humidity: 10-95%
- c) Avoid harmful air, flammable and corrosive things
- d) No vibration, collision, and magnet
- e) Packing box should be 20cm high from ground, away from heat, window and air entrance
- f) Can be stored for 2 years if conditions are all fine
- g) Examination needed after 2 years' storage